

VERIFICATION OF CONSTRUCTION DEVIATIONS USING PARAMETRIC BIM&AR

Michael Jenewein

E259.1 - Institute of Architectural Sciences - Digital Architecture and Planning

INTRODUCTION AND MOTIVATION

This PhD project deals with the detection of constructive deviations between a Building Information Model (BIM) from planning stage and the as-built situation after construction by use of Augmented Reality (AR) directly on the building site. BIM has become a feature in design and planning [1] but with limited investigations how it can be integrated on-site [2]. This work presents an approach for tracking dimensional deviations with BIM&AR.

Reasons for building deviations and the gap between planning model and built model are misinterpreted plans, errors in the building process or deviating decisions of local site management that are not corrected afterwards in the planning database. State of the art in measuring building deviations is surveying with total stations, laser scanners [3] or photogrammetry [4]. Corrections of the planning database by use of measured data are normally made later in the office. This project proposes an approach for integrating AR tracing of existing constructions by comparing as-planned and as-built data in real world on the construction site with the advantage of saving time and costs [5].

REREARCH PROJECT

AR tracing of constructive deviations will only be possible based on a parametric real time model. In this project Unity is used as parametric modeler and Vuforia as implemented AR tool. The individual BIM elements of the database are structured in layers. A scale model with an axis spacing of 12 m by 12 m and a grid of 3 m with standardized industrial components such as truss girders enables to explore simulated deviations in an office environment. The constructive dimensions in the scale model correspond to real-world components.

AR tracking is done by a webcam and a target with additional markers. The AR setup has been optimized by camera calibration and test cases with different viewing angles and lighting conditions. An iPad interface enables wireless remote editing of the parametric BIM&AR database. Measurements can be made directly on-site in AR with a virtual ruler.




Figure 1: Interior AR view of a parametric truss girder




Figure 2: BIM with a scaled truss girder in AR view

RESULTS AND DISCUSSION

Experience shows that the parametric BIM&AR setup is very sensitive to subtle changes of single components. But basically the on-site tracing of construction deviations by comparing as-planned and as-built data with AR works. Technically it is essential to have a calibrated AR setup with AR camera and AR tracking. Lighting conditions and viewing angles also have to be considered. The remote connection to the BIM&AR database via iPad and WiFi enables user independent location on the construction site.

CONCLUSION

Building Information Modeling (BIM) and Augmented Reality (AR) are key technologies for the future. The combination of BIM&AR will enhance the process of as-built information extraction to improve on-site effectiveness [6]. In order to verify the findings of the model stage under real conditions the results of the PhD work will be implemented in an industrial real-world test case in scale 1:1. The planned evaluation in an example environment directly on a construction site will help to derive a robust and reliable method for "Verification of Construction Deviations using Parametric BIM&AR".

REFERENCES

- [1] Automation in Construction, Kristen Barlish and Kenneth Sullivan "How to measure the benefits of BIM — A case study approach", <http://www.sciencedirect.com>, 2012.
- [2] Automation in Construction, Xiangyu Wang and Peter E.D. Love and Mi Jeong Kim and Chan-Sik Park and Chun-Pong Sing and Lei Hou "A conceptual framework for integrating building information modeling with augmented reality", <http://www.sciencedirect.com>, 2012.
- [3] Journal of Civil Engineering and Management, 22 October 2013, p.1-10, Mill, Tarvo and Alt, Aivars and Liias, Roode "Combined 3D building surveying techniques – terrestrial laser scanning (TLS) and total station surveying for BIM data management purposes", <https://journals.vgtu.lt/index.php/JCEM/article/view/3949>, 2013.
- [4] ISPRS - International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences, Tuttas, S. and Braun, A. and Borrmann, A. and Stilla, U. "Comparison of photogrammetric point clouds with BIM building elements for construction progress monitoring", <https://www.int-arch-photogramm-remote-sens-spatial-inf-sci.net/XL-3/341/2014/isprsarchives-XL-3-341-2014.pdf>, 2014.
- [5] Automation in Construction, Xiangyu Wang and Martijn Truijens and Lei Hou and Ying Wang and Ying Zhou "Integrating Augmented Reality with Building Information Modeling: Onsite construction process controlling for liquefied natural gas industry", <http://www.sciencedirect.com>, 2014.
- [6] Automation in Construction, Chu, Michael and Matthews, Jane and Love, Peter E.D. "Integrating mobile Building Information Modelling and Augmented Reality systems: An experimental study", <http://www.sciencedirect.com>, 2017.